

Institutional Series 330Z, Wheel EL

 ROLLENBAU

 max 110 kg  -20 °C - +60 °C  100-150 mm

 swivels easily

 wear resistant

 shock proof

 floor protective

 weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4\Omega$
nylon rim, conductive, volume resistance value $<10^4\Omega$

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 57 mm, stem revited, wheel axle bolted and locked, total/
directional lock – spring stainless steel

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Metal-Technology
- Kitchen equipment
- Food & dish carts
- Food & dish carts
- Workshops
- Laboratory equipment
- Room service carts
- Instrument stands
- School furniture
- Carpentry
- Health-Professionals



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



WITH DIRECTIONAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	STERN MM	TRANSVERSE BORE MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
330 Z18 102 ELK	Swivel castor	100x32	90	132	18x62	M8 auf 30	93		73,20
331 Z18 102 ELK	Swivel castor with total lock	100x32	90	132	18x62	M8 auf 30	118		94,08
337 Z18 102 ELK	Swivel castor with directional lock	100x32	90	132	18x62	M8 auf 30	118		98,16
330 Z18 127 ELK	Swivel castor	125x32	100	158	18x62	M8 auf 30	104		86,52
331 Z18 127 ELK	Swivel castor with total lock	125x32	100	158	18x62	M8 auf 30	130		105,96
337 Z18 127 ELK	Swivel castor with directional lock	125x32	100	158	18x62	M8 auf 30	130		109,08
330 Z18 150 ELK	Swivel castor	150x32	110	187	18x62	M8 auf 30	121		111,36
331 Z18 150 ELK	Swivel castor with total lock	150x32	110	187	18x62	M8 auf 30	121		144,84
337 Z18 150 ELK	Swivel castor with directional lock	150x32	110	187	18x62	M8 auf 30	121		136,80