

Rail wheels - Single-flanged Wheel Series SFH



max 1200 kg -30 °C - +60 °C 100-200 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof



Material

Tread: Vulkollan® 92±3 Shore A, 115° C heat resistant for limited use
Wheel centre - steel BS 3100

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ high chemical resistance

Applications

- Building-Industry

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø WITHOUT FLANGE MM	WHEEL-Ø WITH FLANGE MM	TREAD WIDTH MM	WHEEL WIDTH MM	LOAD CAPACITY KG	HUB WIDTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
100 SFH-20	Rail Wheel	100	125	40	52	500	52		20 H7	461,40
100 SFHK 20	Rail Wheel	100	125	40	52	500	52		20	275,40
125 SFH-20	Rail Wheel	125	155	45	57	600	57		20 H7	267,84
125 SFHK 20	Rail Wheel	125	155	45	57	600	57		20	380,40
150 SFH-20	Rail Wheel	150	190	50	62	900	62		20 H7	auf Anfrage
150 SFHK 20	Rail Wheel	150	190	50	62	900	62		20	auf Anfrage
200 SFH-25	Rail Wheel	200	240	60	75	1200	75		25 H7	819,96
200 SFHK 25	Rail Wheel	200	240	60	75	1200	75		25	885,24