

Rail wheels - Single-flanged Wheel Series SPA



max 380 kg -30 °C - +80 °C 30-120 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof



Material

Single flanged wheel - high quality nylon
tread properly machined
running surface with a 3° gradient

Advantages

- ✓ low rolling resistance
- ✓ high abrasion resistance

Applications

- Building-Industry

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø WITHOUT FLANGE MM	WHEEL-Ø WITH FLANGE MM	TREAD WIDTH MM	WHEEL WIDTH MM	LOAD CAPACITY KG	HUB WIDTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
30 SPA-10	Rail Wheel	30	50	15	20	35	20	==	10	27,96
35 SPA-16	Rail Wheel	35	50	25	32	80	34	==	16	32,88
36 SPA-15	Rail Wheel	35	50	28	37,5	80	38,5	==	15	33,60
40 SPA-15	Rail Wheel	40	55	12	18	40	18	==	15	27,96
50 SPA-16	Rail Wheel	50	70	20	30	100	30	==	16	34,44
51 SPA-15	Rail Wheel	50	65	24	32	100	29	==	15	36,36
52 SPA-10	Rail Wheel	50	65	20	25	90	25	==	10	40,44
50 SPAK 12	Rail Wheel	50	90	26	35	200	10	⊗	12	41,16
62 SPA-16	Rail Wheel	62	75	18	26	100	30	==	16	34,44
63 SPA-16	Rail Wheel	62	80	18	26	100	30	==	16	34,44
62 SPAK 15	Rail Wheel	62	80	19	26,5	160	11	⊗	15	43,92
87 SPA-16	Rail Wheel	87	108	25	32	200	32	==	16	78,12
100 SPA- 20	Rail Wheel	100	120	32	45	280	40	==	20	27,12
120 SPA- 38	Rail Wheel	120	150	30	42	380	45	==	38	126,12