

Rail wheels - Single-flanged Wheel Series SPE



max 4000 kg -30 °C - +80 °C 75-300 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof



Material

Single flanged wheel made of high-compressed semi rigid cast nylon, made of solid material turned running surface with a 3° gradient

Advantages

- ✓ low rolling resistance
- ✓ high abrasion resistance
- ✓ very high load capacity

Applications

- Building-Industry

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø WITHOUT FLANGE MM	WHEEL-Ø WITH FLANGE MM	TREAD WIDTH MM	WHEEL WIDTH MM	LOAD CAPACITY KG	HUB WIDTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
75 SPEK 20	Rail Wheel	75	100	30	40	380	40		20	142,20
100 SPEK 20	Rail Wheel	100	125	36	46	600	46		20	196,08
125 SPEK 20	Rail Wheel	125	145	36	46	750	46		20	209,64
150 SPEK 30	Rail Wheel	150	175	38	52	950	52		30	254,88
200 SPEK 40	Rail Wheel	200	230	48	60	1600	60		40	346,08
201 SPEK 40	Rail Wheel	200	230	65	80	2200	80		40	511,32
250 SPEK 50	Rail Wheel	250	290	60	75	3000	75		50	879,24
300 SPEK 60	Rail Wheel	300	340	72	90	4000	90		60	1262,76