

Spring-loaded Castors Series MFA, Wheel Z



max 260 kg -30 °C - +80 °C 100-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Tread: Cast polyurethane, 95±3 Shore A
Wheel centre, Cast-iron - painted

Material Fork



Medium duty spring castors Finish: black painted, Polyurethane buffer spring, double ball bearing, equaliser swinging on bronze bushes

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Decoration carts
- Stage equipment



SWIVEL CASTOR



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	PRELOAD FORCE DAN	MAX.SPRING TRAVEL MM	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
MFA 101 ZK	Swivel castor	100x40	130	40	25	171	105x85	80x60	11	82		290,28
MFFA 101 ZK	Fixed castor	100x40	130	40	25	171	105x85	80x60	11			226,80
MFB 101 ZK	Swivel castor	100x40	170	50	25	171	105x85	80x60	11	82		284,28
MFFB 101 ZK	Fixed castor	100x40	170	50	25	171	105x85	80x60	11			234,48
MFC 101 ZK	Swivel castor	100x40	170	50	25	171	135x110	105x80	13	82		287,40
MFFC 101 ZK	Fixed castor	100x40	170	50	25	171	135x110	105x80	13			225,60
MFA 125 ZK	Swivel castor	125x30	200	90	25	207	105x85	80x60	11	96		287,40
MFFA 125 ZK	Fixed castor	125x30	200	90	25	207	105x85	80x60	11			230,16
MFB 125 ZK	Swivel castor	125x30	200	90	25	207	135x110	105x80	13	96		287,40
MFFB 125 ZK	Fixed castor	125x30	200	90	25	207	135x110	105x80	13			229,80
MFA 150 ZK	Swivel castor	150x40	220	90	28	233	135x110	105x80	13	120		351,12
MFFA 150 ZK	Fixed castor	150x40	220	90	28	233	135x110	105x80	13			293,52
MFA 200 ZK	Swivel castor	200x50	260	85	32	274	135x110	105x80	13	159		381,84
MFFA 200 ZK	Fixed castor	200x50	260	85	32	274	135x110	105x80	13			324,00