

Stainless Steel Series 310XP, Wheel



max 50 kg -20 °C - +60 °C 50-100 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Standard rubber tyre grey
Nylon rim

Material Fork



Finish: Polished stainless steel, large double ball bearing – Ø 46 mm, bolted, wheel axle bolted and locked, adjustable total lock

Advantages

- ✓ non-marking - floor protective
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Mechatronik
- Wet environments
- Health-Professionals

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
310X PT 50 G	Swivel castor	50x18	40	75	60x60	40x40/46x46	7	53	=	59,64
312X PT 50 G	Swivel castor with total lock	50x18	40	75	60x60	40x40/46x46	7	85	=	110,52
310X PT 75 G	Swivel castor	75x25	45	103	60x60	40x40/46x46	7	69	=	64,92
312X PT 75 G	Swivel castor with total lock	75x25	45	103	60x60	40x40/46x46	7	85	=	116,28
310X PT 100 G	Swivel castor	100x25	50	125	60x60	40x40/46x46	7	86	=	82,80
312X PT 100 G	Swivel castor with total lock	100x25	50	125	60x60	40x40/46x46	7	86	=	128,28