

Stainless Steel Series 310XP, Wheel



max 45 kg -20 °C - +60 °C 50-75 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Tread: Thermoplastic elastomer coating 95±3 Shore A**
High quality nylon wheel centre

Material Fork



Finish: Polished stainless steel, large double ball bearing – Ø 46 mm, bolted, wheel axle bolted and locked, adjustable total lock

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high resistance to shocks
- ✓ non-marking
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Wet environments
- Health-Professionals

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
310X PT 50 V	Swivel castor	50x18	40	75	60x60	40x40/46x46	7	53		60,24
312X PT 50 V	Swivel castor with total lock	50x18	40	75	60x60	40x40/46x46	7	85		106,92
310X PT 75 TPKX	Swivel castor	75x25	45	103	60x60	40x40/46x46	7	69		106,68
312X PT 75 TPKX	Swivel castor with total lock	75x25	45	103	60x60	40x40/46x46	7	85		148,92