

Stainless Steel Series 310XR, Wheel



max 50 kg -20 °C - +60 °C 50-100 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4\Omega$
nylon rim, conductive, volume resistance value $<10^4\Omega$

Material Fork



Finish: Polished stainless steel swivel fork with single bolt hole,
large double ball bearing – Ø 46 mm, revited, wheel axle bolted
and locked, adjustable total lock

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Mechatronik
- Wet environments
- Health-Professionals

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
310X RÜ 50 EL	Swivel castor	50x18	40	75	10,2	53	==	74,88
312X RÜ 50 EL	Swivel castor with total lock	50x18	40	75	10,2	85	==	119,76
310X RÜ 75 EL	Swivel castor	75x25	45	103	10,2	69	==	79,56
312X RÜ 75 EL	Swivel castor with total lock	75x25	45	103	10,2	85	==	125,40
310X RÜ 100 EL	Swivel castor	100x25	50	125	10,2	86	==	103,80
312X RÜ 100 EL	Swivel castor with total lock	100x25	50	125	10,2	86	==	137,16