

Stainless Steel Series 310XR, Wheel



max 45 kg -20 °C - +60 °C 50-75 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Tread: Thermoplastic elastomer coating 95±3 Shore A**
High quality nylon wheel centre

Material Fork



Finish: Polished stainless steel swivel fork with single bolt hole,
large double ball bearing – Ø 46 mm, revited, wheel axle bolted
and locked, adjustable total lock

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high resistance to shocks
- ✓ non-marking
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Wet environments
- Health-Professionals

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
310X RÜ 50 V	Swivel castor	50x18	40	75	10,2	53		54,72
312X RÜ 50 V	Swivel castor with total lock	50x18	40	75	10,2	85		95,52
310X RÜ 75 TPKX	Swivel castor	75x25	45	103	10,2	69		96,48
312X RÜ 75 TPKX	Swivel castor with total lock	75x25	45	103	10,2	85		139,92