

Stainless Steel Series 330LXR, Wheel



max 100 kg -20 °C - +60 °C 100-125 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Tread: Thermoplastic elastomer coating 95±3 Shore A**
High quality nylon wheel centre

Material Fork



Stainless steel swivel fork with single bolt hole, large double ball bearing – Ø 57 mm, revited, wheel axle bolted and locked, total lock

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high resistance to shocks
- ✓ non-marking
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Food & dish carts
- Food service carts
- Food & dish carts
- Food service carts
- Wet environments
- Health-Professionals

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
330LX RÜ10 102 TPKX	Swivel castor	100x32	90	132	10,5	90		80,88
331LX RÜ10 102 TPKX	Swivel castor with total lock	100x32	90	132	10,5	130		99,96
330LX RÜ10 102 TP	Swivel castor	100x32	90	132	10,5	90		72,36
331LX RÜ10 102 TP	Swivel castor with total lock	100x32	90	132	10,5	130		91,08
330LX RÜ12 102 TPKX	Swivel castor	100x32	90	132	13	90		80,88
331LX RÜ12 102 TPKX	Swivel castor with total lock	100x32	90	132	13	130		99,96
330LX RÜ12 102 TP	Swivel castor	100x32	90	132	13	90		74,52
331LX RÜ12 102 TP	Swivel castor with total lock	100x32	90	132	13	130		93,36
330LX RÜ10 127 TPKX	Swivel castor	125x32	100	158	10,5	103		102,72
331LX RÜ10 127 TPKX	Swivel castor with total lock	125x32	100	158	10,5	130		112,80
330LX RÜ10 127 TP	Swivel castor	125x32	100	158	10,5	103		79,32
331LX RÜ10 127 TP	Swivel castor with total lock	125x32	100	158	10,5	130		98,16
330LX RÜ12 127 TPKX	Swivel castor	125x32	100	158	13	103		88,92
331LX RÜ12 127 TPKX	Swivel castor with total lock	125x32	100	158	13	130		112,80
330LX RÜ12 127 TP	Swivel castor	125x32	100	158	13	103		79,32
331LX RÜ12 127 TP	Swivel castor with total lock	125x32	100	158	13	130		98,16