

Stainless Steel Series 330LXZ, Wheel



max 100 kg -20 °C - +60 °C 100-125 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4\Omega$
nylon rim, conductive, volume resistance value $<10^4\Omega$

Material Fork



Stainless steel swivel fork with single bolt hole, large double ball
bearing – Ø 57 mm, revited, wheel axle bolted and locked, total
lock

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Food & dish carts
- Food service carts
- Food & dish carts
- Food service carts
- Wet environments
- Health-Professionals

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	STERN MM	TRANSVERSE BORE MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
330LX Z18 102 ELKX	Swivel castor	100x32	90	132	18x62	M6 auf 19	90		99,36
331LX Z18 102 ELKX	Swivel castor with total lock	100x32	90	132	18x62	M6 auf 19	130		117,36
330LX Z18 102 EL	Swivel castor	100x32	90	132	18x62	M6 auf 19	90		90,48
331LX Z18 102 EL	Swivel castor with total lock	100x32	90	132	18x62	M6 auf 19	130		108,60
330LX Z18 127 ELKX	Swivel castor	125x32	100	158	18x62	M6 auf 30	103		110,28
331LX Z18 127 ELKX	Swivel castor with total lock	125x32	100	158	18x62	M6 auf 19	130		128,40
330LX Z18 127 EL	Swivel castor	125x32	100	158	18x62	M6 auf 3	103		100,32
331LX Z18 127 EL	Swivel castor with total lock	125x32	100	158	18x62	M6 auf 19	130		118,80