

Stainless Steel Series IN, Wheel PS



max 250 kg -30 °C - +80 °C 100-200 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Cast soft polyurethane coating,
87±3 Shore A
High quality nylon wheel centre

Material Fork



Finish: Polished stainless steel, swivel fork with top plate, double ball bearing – bolted, with dust protection ring, wheel axle bolted – locked, adjustable total lock

Advantages

- ✓ very silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Wet environments
- Dollies



SWIVEL CASTOR



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
INV 100 PSBX	Swivel castor	100x40	250	125	135x110	105x80	11	102		155,16
INVF 100 PSBX	Fixed castor	100x40	250	125	135x110	105x80	11			93,12
IN 100 PSBX	Swivel castor	100x33	125	125	105x85	80x60	9	96		108,84
INF 100 PSBX	Fixed castor	100x33	125	125	105x85	80x60	9			59,28
IN 125 PSBX	Swivel castor	125x35	175	155	135x110	105x80	11	114		167,88
INF 125 PSBX	Fixed castor	125x35	175	155	135x110	105x80	11			88,56
IN 150 PSBX	Swivel castor	150x40	210	180	135x110	105x80	11	127		190,92
INF 150 PSBX	Fixed castor	150x40	210	180	135x110	105x80	11			129,60
IN 200 PSBX	Swivel castor	200x50	400	230	135x110	105x80	11	162		228,12
INF 200 PSBX	Fixed castor	200x50	400	230	135x110	105x80	11			159,96