

Stainless Steel Series INSS, Wheel A



 max 800 kg  -30 °C - +80 °C  125-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Coated in cast polyurethane, 95±3 Shore A
High quality nylon wheel centre

Material Fork



Finish: Polished stainless steel, welded stainless steel swivel fork without Kingpin, large diameter swivel raceway, fully sealed double ball race with permanent grease fillings, wheel axle bolted, adjustable total lock

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Wet environments

 ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
INSS 126 A	Swivel castor	125x45	250	165	140x127	114x105	11	115	==	506,76
INSST 126 A	Swivel castor with total lock	125x45	250	165	140x127	114x105	11	115	==	751,68
INFSS 126 A	Fixed castor	125x45	250	165	140x127	114x105	11		==	277,92
INSS 150 A	Swivel castor	150x48	400	200	150x150	125x125	11	132	==	561,12
INSST 150 A	Swivel castor with total lock	150x48	400	200	150x150	125x125	11	132	==	734,88
INFSS 150 A	Fixed castor	150x48	400	200	150x150	125x125	11		==	321,00
INSS 150 AA	Swivel castor	150x48+48	800	205	150x150	125x125	11	139	==	633,72
INFSS 150 AA	Fixed castor	150x48+48	800	205	150x150	125x125	11		==	366,36
INSS 200 A	Swivel castor	200x50	600	241	150x150	125x125	11	167	==	729,24
INSST 200 A	Swivel castor with total lock	200x50	600	241	150x150	125x125	11	167	==	860,64
INFSS 200 A	Fixed castor	200x50	600	241	150x150	125x125	11		==	433,20