

Stainless Steel Series XR, Wheel PS



max 300 kg -30 °C - +80 °C 100-200 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Cast soft polyurethane coating,
87±3 Shore A
High quality nylon wheel centre

Material Fork



Finish: Polished stainless steel swivel fork AISI 304, stainless steel balls AISI 420, double ball bearing – revited, wheel axle bolted, total lock

Advantages

- ✓ very silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Kitchen equipment
- Mechatronik
- Wet environments

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
XRS 100 PSBX	Swivel castor	100x40	250	129	12,5	98		106,08
XRST 100 PSBX	Swivel castor with total lock	100x40	250	129	12,5	140		139,92
XRS 125 PSBX	Swivel castor	125x40	250	160	12,5	113		120,00
XRST 125 PSBX	Swivel castor with total lock	125x40	250	160	12,5	140		153,72
XR 150 PSBX	Swivel castor	150x40	250	181	12,5	128		132,48
XRT 150 PSBX	Swivel castor with total lock	150x40	250	181	12,5	140		166,32
XR 200 PSBX	Swivel castor	200x50	300	240	12,5	161		212,88
XRT 200 PSBX	Swivel castor with total lock	200x50	300	240	12,5	168		258,00