

Stainless Steel Series XR, Wheel D



 max 205 kg  -20 °C - +60 °C  80-200 mm


swivels easily


wear resistant


shock proof


floor protective


weather proof

Material



Tread: standard rubber tyre black, 85±5 Shore A

Quality nylon wheel centre

Material Fork



Finish: Polished stainless steel swivel fork AISI 304, stainless steel balls AISI 420, double ball bearing – revited, wheel axle bolted, total lock

Advantages

- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Wet environments



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
XR 80 D	Swivel castor	80x30	50	106	12,5	75	==	41,76
XRT 80 D	Swivel castor with total lock	80x30	50	106	12,5	108	==	62,52
XR 100 D	Swivel castor	100x30	75	128	12,5	88	==	44,16
XRT 100 D	Swivel castor with total lock	100x30	75	128	12,5	108	==	65,76
XR 125 D	Swivel castor	125x38	90	154	12,5	104	==	48,48
XRT 125 D	Swivel castor with total lock	125x38	90	154	12,5	108	==	69,72
XR 150 D	Swivel castor	150x40	125	181	12,5	128	==	78,84
XRT 150 D	Swivel castor with total lock	150x40	125	181	12,5	140	==	104,76
XR 200 D	Swivel castor	200x50	205	240	12,5	161	==	121,92
XRT 200 D	Swivel castor with total lock	200x50	205	240	12,5	168	==	163,32