

Stainless Steel Series XR, Wheel AEL



max 300 kg -20 °C - +70 °C 80-200 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



coated in polyurethane, 90±3 Shore A electrically conductive
<10⁴Ω
High quality nylon wheel centre

Material Fork



Finish: Polished stainless steel swivel fork AISI 304, stainless steel balls AISI 420, double ball bearing – revited, wheel axle bolted, total lock

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ low rolling resistance
- ✓ non-marking
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Mechatronik
- Wet environments

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICLE TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
XR 80 AELK	Swivel castor	80x32	120	106	12,5	75		68,16
XRT 80 AELK	Swivel castor with total lock	80x32	120	106	12,5	108		93,72
XR 100 AELK	Swivel castor	100x32	120	128	12,5	88		84,48
XRT 100 AELK	Swivel castor with total lock	100x32	120	128	12,5	108		105,96
XRS 100 AELK	Swivel castor	100x32	200	129	12,5	98		88,92
XRST 100 AELK	Swivel castor with total lock	100x32	200	129	12,5	140		110,04
XR 125 AELK	Swivel castor	125x32	120	154	12,5	104		106,08
XRT 125 AELK	Swivel castor with total lock	125x32	120	154	12,5	108		124,32
XRS 125 AELK	Swivel castor	125x46	200	160	12,5	114		196,08
XRST 125 AELK	Swivel castor with total lock	125x46	200	160	12,5	140		171,00
XR 200 AELK	Swivel castor	200x50	300	240	12,5	161		291,48
XRT 200 AELK	Swivel castor with total lock	200x50	300	240	12,5	168		418,80