

Stainless Steel Series XR, Wheel EL



max 205 kg -20 °C - +60 °C 80-200 mm

++
swivels easily

++
wear resistant

++
shock proof

++
floor protective

++
weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4\Omega$
bolte stainless steel rim, volume resistance value $<10^4\Omega$

Material Fork



Finish: Polished stainless steel swivel fork AISI 304, stainless
steel balls AISI 420, double ball bearing – revited, wheel axle
bolted, total lock

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Wet environments

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
XR 80 ELBX	Swivel castor	80x25	50	106	12,5	74		90,72
XRT 80 ELBX	Swivel castor with total lock	80x25	50	106	12,5	108		115,08
XR 100 ELBX	Swivel castor	100x30	100	128	12,5	88		100,32
XRT 100 ELBX	Swivel castor with total lock	100x30	100	128	12,5	108		123,24
XRS 125 ELBX	Swivel castor	125x38	100	160	12,5	113		142,44
XRST 125 ELBX	Swivel castor with total lock	125x38	100	160	12,5	140		170,04
XR 200 ELBX	Swivel castor	200x50	205	240	12,5	161		249,36
XRT 200 ELBX	Swivel castor with total lock	200x50	205	240	12,5	168		291,48