

Transport Series BCD, Wheel RBB

 max 200 kg  -30 °C - +80 °C  80-125 mm

 **swivels easily**

 **wear resistant**

 **shock proof**

 **floor protective**

 **weather proof**

Material



Tread: standard rubber tyre black, 85±5 Shore A

Quality nylon wheel centre

Material Fork



Finish: electro-zinc plated and yellow passivated, double ball bearing - revited, hardened steel balls, thermoplastic dust protection ring, wheel axle bolted, total lock, black

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Platform trucks
- Mobile tool racks
- Bins
- Tow line trucks
- Tow-line trucks
- Chair dollies
- Table dollies
- Furniture dollies
- Refuse bins
- Delivery containers
- Dollies
- Trash containers
- Refuse containers

 **ROLLENBAU**



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
BCD 80 RBB	Swivel castor	80x35	100	100	105x85	80x60		82		41,76
BCDT 80 RBB	Swivel castor with total lock	80x35	100	100	105x85	80x60		126		51,36
BCDF 80 RBB	Fixed castor	80x35	100	100	105x85	80x60				34,80
BCD 100 RBB	Swivel castor	100X36	150	125	105x85	80x60		91		46,56
BCDT 100 RBB	Swivel castor with total lock	100X36	100	100	105x85	80x60		126		61,44
BCDF 100 RBB	Fixed castor	100X36	100	100	105x85	80x60				38,64
BCD 125 RBB	Swivel castor	125X36	200	155	105x85	80x60		99		60,96
BCDT 125 RBB	Swivel castor with total lock	125X36	200	155	105x85	80x60		140		76,80
BCDF 125 RBB	Fixed castor	125X36	200	155	105x85	80x60				53,52