

Transport Series CD, Wheel TLS



max 300 kg -20 °C - +80 °C 125-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Tread: cast polyurethane, 70±3 Shore A
Core: Die-cast aluminium alloy

Material Fork



Finish: electro-zinc plated, double ball bearing – revited, hardened steel balls thermoplastic dust protection ring, wheel axle bolted, total lock

Advantages

- ✓ very silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Metal-Technology
- Workshops
- Dollies
- Carpentry
- Building-Industry



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CSS 125 TLSK	Swivel castor	125x50	200	160	135x110	105x80	12.5	114		86,04
CSST 125 TLSK	Swivel castor with total lock	125x50	200	160	135x110	105x80	12.5	140		116,52
CSSF 125 TLSK	Fixed castor	125x50	200	160	135x110	105x80	12.5			76,32
CS 150 TLSK	Swivel castor	150x50	200	191	135x110	105x80	11	133		114,72
CST 150 TLSK	Swivel castor with total lock	150x50	200	191	135x110	105x80	11	168		135,72
CSF 150 TLSK	Fixed castor	150x50	200	191	135x110	105x80	11			94,08
CD 200 TLSK	Swivel castor	200x50	300	240	135x110	105x80	11	161		168,60
CDT 200 TLSK	Swivel castor with total lock	200x50	300	240	135x110	105x80	11	168		182,40
CDF 200 TLSK	Fixed castor	200x50	300	240	135x110	105x80	11			156,24