

Transport Series CD, Wheel TLSBA

 max 300 kg  -20 °C - +80 °C  125-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Tread: cast polyurethane, 85 ± 2 Shore A crowned - soft
Core: Die-cast aluminium alloy

Material Fork



Finish: electro-zinc plated, double ball bearing – revited, hardened
steel balls thermoplastic dust protection ring, wheel axle bolted,
total lock

Advantages

- ✓ crowned soft tread makes it very economic
- ✓ very silent in motion
- ✓ very low rolling resistance
- ✓ very revving
- ✓ high abrasion and tear resistance
- ✓ good chemical resistance

Applications

- Metal-Technology
- Workshops
- Dollies
- Carpentry
- Building-Industry

 ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICLE TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CSS 125 TLSBAK	Swivel castor	125x50	200	160	135x110	105x80	11	114		134,52
CSST 125 TLSBAK	Swivel castor with total lock	125x50	200	160	135x110	105x80	11	140		147,84
CSSF 125 TLSBAK	Fixed castor	125x50	200	160	135x110	105x80	11			123,60
CS 150 TLSBAK	Swivel castor	150x50	200	191	135x110	105x80	11	133		152,04
CST 150 TLSBAK	Swivel castor with total lock	150x50	200	191	135x110	105x80	11	168		167,52
CSF 150 TLSBAK	Fixed castor	150x50	200	191	135x110	105x80	11			138,00
CD 200 TLSBAK	Swivel castor	200x50	300	240	135x110	105x80	11	161		177,12
CDT 200 TLSBAK	Swivel castor with total lock	200x50	300	240	135x110	105x80	11	168		195,48
CDF 200 TLSBAK	Fixed castor	200x50	300	240	135x110	105x80	11			163,32