

Transport Series CD, Wheel EL

 max 205 kg  -20 °C - +60 °C  80-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4 \Omega$
bolted steel rim zinc plated, volume resistance value $<10^4 \Omega$

Material Fork



Finish: electro-zinc plated, double ball bearing – revited, hardened
steel balls thermoplastic dust protection ring, wheel axle bolted,
total lock

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Diagnostic equipment
- Automobile test equipment

 ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CD 80 ELB	Swivel castor	80x25	50	106	102x83	80x60	9	74		43,92
CDT 80 ELB	Swivel castor with total lock	80x25	50	106	102x83	80x60	9	108		56,04
CDF 80 ELB	Fixed castor	80x25	50	106	102x83	80x60	9			37,92
CD 100 ELB	Swivel castor	100x30	70	128	102x83	80x60	9	88		50,40
CDT 100 ELB	Swivel castor with total lock	100x30	70	128	102x83	80x60	9	108		64,80
CDF 100 ELB	Fixed castor	100x30	70	128	102x83	80x60	9			43,92
CS 125 ELB	Swivel castor	125x38	100	160	102x83	80x60	9	113		68,88
CST 125 ELB	Swivel castor with total lock	125x38	100	160	102x83	80x60	9	140		82,92
CSF 125 ELB	Fixed castor	125x38	100	160	102x83	80x60	9			62,52
CSS 125 ELB	Swivel castor	125x38	100	160	135x110	105x80	11	113		70,92
CSST 125 ELB	Swivel castor with total lock	125x38	100	160	135x110	105x80	11	140		85,20
CSSF 125 ELB	Fixed castor	125x38	100	160	135x110	105x80	11			64,56
CD 160 ELK	Swivel castor	160x40	135	191	135x110	105x80	11	133		95,52
CDT 160 ELK	Swivel castor with total lock	160x40	135	191	135x110	105x80	11	140		112,56
CDF 160 ELK	Fixed castor	160x40	135	191	135x110	105x80	11			82,80
CD 160 ELB	Swivel castor	160x40	135	191	135x110	105x80	11	133		80,40
CDT 160 ELB	Swivel castor with total lock	160x40	135	191	135x110	105x80	11	140		96,72
CDF 160 ELB	Fixed castor	160x40	135	191	135x110	105x80	11			67,44
CD 200 ELK	Swivel castor	200x50	205	240	135x110	105x80	11	161		130,92
CDT 200 ELK	Swivel castor with total lock	200x50	205	240	135x110	105x80	11	168		152,04
CDF 200 ELK	Fixed castor	200x50	205	240	135x110	105x80	11			116,04
CD 200 ELB	Swivel castor	200x50	205	240	135x110	105x80	11	161		115,92
CDT 200 ELB	Swivel castor with total lock	200x50	205	240	135x110	105x80	11	168		137,04
CDF 200 ELB	Fixed castor	200x50	205	240	135x110	105x80	11			100,92