

Transport Series CR, Wheel TLSBA



max 300 kg -20° C - +80 °C 125-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Tread: cast polyurethane, 85 ± 2 Shore A crowned - soft
Core: Die-cast aluminium alloy

Material Fork



Medium duty bolt hole castor, finish: electro-zinc plated and yellow passivated, swivel fork with single bolt hole, double ball bearing – revited, hardened steel balls, wheel axle bolted, total lock

Advantages

- ✓ crowned soft tread makes it very economic
- ✓ very silent in motion
- ✓ very low rolling resistance
- ✓ very revving
- ✓ high abrasion and tear resistance
- ✓ good chemical resistance

Applications

- Metal-Technology
- Workshops
- Carpentry
- Building-Industry



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CRS 125 TLSBAK	Swivel castor	125x50	200	160	12,5	114		130,92
CRST 125 TLSBAK	Swivel castor with total lock	125x50	200	160	12,5	140		145,44
CRS 150 TLSBAK	Swivel castor	150x50	200	191	12,5	133		147,84
CRST 150 TLSBAK	Swivel castor with total lock	150x50	200	191	12,5	168		162,96
CR 200 TLSBAK	Swivel castor	200x50	300	240	12,5	161		173,40
CRT 200 TLSBAK	Swivel castor with total lock	200x50	300	240	12,5	168		186,72