

Transport Series CR, Wheel AEL ⚡

ROLLENBAU

max 300 kg -20 °C - +70 °C 80-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



coated in polyurethane, 90±3 Shore A electrically conductive
<10⁴Ω
High quality nylon wheel centre

Material Fork



Medium duty bolt hole castor, finish: electro-zinc plated and yellow passivated, swivel fork with single bolt hole, double ball bearing – revited, hardened steel balls, wheel axle bolted, total lock

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ low rolling resistance
- ✓ non-marking
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Tyre racks



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICLE TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CR 80 AELK	Swivel castor	80x32	120	106	12,5	75		48,72
CRT 80 AELK	Swivel castor with total lock	80x32	120	106	12,5	108		61,44
CR 100 AELK	Swivel castor	100x32	120	128	12,5	88		77,16
CRT 100 AELK	Swivel castor with total lock	100x32	120	128	12,5	108		89,88
CRS 100 AELK	Swivel castor	100x32	200	129	12,5	98		72,36
CRST 100 AELK	Swivel castor with total lock	100x32	200	129	12,5	140		81,72
CR 125 AELK	Swivel castor	125x32	120	154	12,5	113		85,80
CRT 125 AELK	Swivel castor with total lock	125x32	120	154	12,5	140		105,96
CRS 125 AELK	Swivel castor	125x46	200	160	12,5	114		117,24
CRST 125 AELK	Swivel castor with total lock	125x46	200	160	12,5	140		134,28
CR 160 AELK	Swivel castor	160x46	200	191	12,5	133		142,20
CRT 160 AELK	Swivel castor with total lock	160x46	200	191	12,5	168		130,20
CRS 160 AELK	Swivel castor	160x46	300	195	12,5	138		142,20
CRST 160 AELK	Swivel castor with total lock	160x46	300	195	12,5	168		163,80
CR 200 AELK	Swivel castor	200x50	300	240	12,5	161		164,76
CRT 200 AELK	Swivel castor with total lock	200x50	300	240	12,5	168		264,96