

Transport Series CR, Wheel EBA



max 300 kg -30 °C - +80 °C 125-200 mm

swivels easily	wear resistant	shock proof
floor protective	weather proof	

Material



SUPER-Elastic solid rubber tyre black 55 ± 3 Shore A soft, crowned treat
Core in die-cast aluminium alloy

Material Fork



Medium duty bolt hole castor, finish: electro-zinc plated and yellow passivated, swivel fork with single bolt hole, double ball bearing – revited, hardened steel balls, wheel axle bolted, total lock

Advantages

- ✓ very silent in motion
- ✓ very low rolling resistance
- ✓ good abrasion resistance
- ✓ corrosion resistant
- ✓ alternative to pneumatic tires

Applications

- Tyre racks
- Mobile tool racks
- Furniture dollies



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CR 125 EBAK	Swivel castor	125X40	200	154	12,5	104		50,52
CRT 125 EBAK	Swivel castor with total lock	125X40	200	154	12,5	108		63,48
CRS 125 EBAK	Swivel castor	125x40	200	160	12,5	113		57,00
CRST 125 EBAK	Swivel castor with total lock	125x40	200	160	12,5	140		71,16
CR 150 EBAK	Swivel castor	150X47	200	181	12,5	128		73,20
CRT 150 EBAK	Swivel castor with total lock	150X47	200	181	12,5	140		87,84
CRS 160 EBAK	Swivel castor	160X50	270	196	12,5	138		87,00
CRST 160 EBAK	Swivel castor with total lock	160X50	270	196	12,5	168		101,88
CR 200 EBAK	Swivel castor	200X50	300	240	12,5	161		103,92
CRT 200 EBAK	Swivel castor with total lock	200X50	300	240	12,5	168		120,96