

Transport Series CR, Wheel EGBA



max 300 kg -30 °C - +80 °C 125-200 mm

swivels easily	wear resistant	shock proof
floor protective	weather proof	

Material



SUPER-Elastic solid rubber tyre black 55 ± 3 Shore A soft, crowned treat
Core in die-cast aluminium alloy

Material Fork



Medium duty bolt hole castor, finish: electro-zinc plated and yellow passivated, swivel fork with single bolt hole, double ball bearing – revited, hardened steel balls, wheel axle bolted, total lock

Advantages

- ✓ very silent in motion
- ✓ very low rolling resistance
- ✓ good abrasion resistance
- ✓ corrosion resistant
- ✓ alternative to pneumatic tires
- ✓ non-marking

Applications

- Tyre racks
- Mobile tool racks
- Chair dollies
- Furniture dollies



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CR 125 EGBAK	Swivel castor	125X40	200	154	12,5	104		51,12
CRT 125 EGBAK	Swivel castor with total lock	125X40	200	154	12,5	108		64,08
CRS 125 EGBAK	Swivel castor	125x40	200	160	12,5	113		61,92
CRST 125 EGBAK	Swivel castor with total lock	125x40	200	160	12,5	140		77,52
CR 150 EGBAK	Swivel castor	150X47	200	181	12,5	128		74,88
CRT 150 EGBAK	Swivel castor with total lock	150X47	200	181	12,5	140		92,04
CRS 160 EGBAK	Swivel castor	160X50	270	196	12,5	138		88,08
CRST 160 EGBAK	Swivel castor with total lock	160X50	270	196	12,5	168		103,08
CR 200 EGBAK	Swivel castor	200X50	300	240	12,5	161		107,04
CRT 200 EGBAK	Swivel castor with total lock	200X50	300	240	12,5	168		124,92