

Transport Series CR, Wheel ELPG ⚡

ROLLENBAU

max 300 kg $-10^{\circ}\text{C} - +60^{\circ}\text{C}$ 125-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Elastic solid rubber tyre 70 ± 5 Shore A electrically conductive
volume resistance value $<10^4\Omega$
High quality nylon wheel centre electrically conductive
volume resistance value $<10^4\Omega$

Material Fork



Medium duty bolt hole castor, finish: electro-zinc plated and yellow passivated, swivel fork with single bolt hole, double ball bearing – revited, hardened steel balls, wheel axle bolted, total lock

Advantages

- ✓ electrically conductive
- ✓ excellent running performance
- ✓ low rolling resistance
- ✓ good abrasion resistance
- ✓ korrosionsbeständig
- ✓ non-marking

Applications

- Diagnostic equipment
- Automobile test equipment



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CRS 125 ELPGB	Swivel castor	125x40	200	163	12,5	113		85,44
CRST 125 ELPGB	Swivel castor with total lock	125x40	200	163	12,5	140		97,56
CRS 160 ELPGK	Swivel castor	160x45	300	199	12,5	138		125,16
CRST 160 ELPGK	Swivel castor with total lock	160x45	300	199	12,5	168		146,64
CR 200 ELPGK	Swivel castor	200x50	300	249	12,5	161		160,44
CRT 200 ELPGK	Swivel castor with total lock	200x50	300	249	12,5	168		177,12