

Transport Series CR, Wheel EL

 ROLLENBAU

 max 205 kg  -20 °C - +60 °C  80-200 mm

 swivels easily

 wear resistant

 shock proof

 floor protective

 weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4\Omega$
bolted steel rim zinc plated, volume resistance value $<10^4\Omega$

Material Fork



Medium duty bolt hole castor, finish: electro-zinc plated and
yellow passivated, swivel fork with single bolt hole, double ball
bearing – revited, hardened steel balls, wheel axle bolted, total
lock

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Diagnostic equipment
- Automobile test equipment



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CR 80 ELB	Swivel castor	80x25	60	106	12,5	74		45,60
CRT 80 ELB	Swivel castor with total lock	80x25	60	106	12,5	108		61,08
CR 100 ELB	Swivel castor	100x30	120	128	12,5	88		50,40
CRT 100 ELB	Swivel castor with total lock	100x30	120	128	12,5	108		64,44
CRS 125 ELB	Swivel castor	125x38	130	160	12,5	113		68,16
CRST 125 ELB	Swivel castor with total lock	125x38	130	160	12,5	140		82,32
CR 160 ELK	Swivel castor	160x40	180	191	12,5	133		96,36
CRT 160 ELK	Swivel castor with total lock	160x40	180	191	12,5	168		112,92
CR 160 ELB	Swivel castor	160x40	180	191	12,5	133		78,36
CRT 160 ELB	Swivel castor with total lock	160x40	180	191	12,5	168		95,04
CR 200 ELK	Swivel castor	200x50	205	240	12,5	161		99,96
CRT 200 ELK	Swivel castor with total lock	200x50	205	240	12,5	168		120,96
CR 200 ELB	Swivel castor	200x50	205	240	12,5	161		106,08
CRT 200 ELB	Swivel castor with total lock	200x50	205	240	12,5	168		126,84