

Transport Series KD, Wheel TLS



max 450 kg -20 °C - +80 °C 125-200 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Tread: cast polyurethane, 70±3 Shore A
Core: Die-cast aluminium alloy

Material Fork



Finish: electro-zinc plated, hardened steel balls, double ball race
swivel head – pressed steel sheet, with strong Kingpin bolted and
locked – adjustable, thermoplastic dust protection ring and seal,
wheel axle bolted, adjustable total lock – leading or trailing
available

Advantages

- ✓ very silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Metal-Technology
- Trash container trucks
- Workshops
- Dye trucks
- Dollies
- Carpentry
- Building-Industry



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
KD 125 TLSK	Swivel castor	125x50	300	173	135x110	105x80	10,5	118		96,24
KDT 125 TLSK	Swivel castor with total lock	125x50	300	173	135x110	105x80	10,5	170		120,00
KDF 125 TLSK	Fixed castor	125x50	300	173	135x110	105x80	10,5			79,20
KD 150 TLSK	Swivel castor	150x50	400	207	135x110	105x80	10,5	126		117,36
KDT 150 TLSK	Swivel castor with total lock	150x50	400	207	135x110	105x80	10,5	140		140,88
KDF 150 TLSK	Fixed castor	150x50	400	207	135x110	105x80	10,5			100,20
KD 200 TLSK	Swivel castor	200x50	450	249	135x110	105x80	12,5	167		175,32
KDT 200 TLSK	Swivel castor with total lock	200x50	450	249	135x110	105x80	12,5	170		218,88
KDF 200 TLSK	Fixed castor	200x50	450	249	135x110	105x80	12,5			142,92