

Transport Series KD, Wheel ELPG ⚡

ROLLENBAU

KG max 450 kg | -10 °C - +60 °C | 125-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Elastic solid rubber tyre 70 ± 5 Shore A electrically conductive
volume resistance value $<10^4 \Omega$
High quality nylon wheel centre electrically conductive
volume resistance value $<10^4 \Omega$

Material Fork



Finish: electro-zinc plated, hardened steel balls, double ball race
swivel head – pressed steel sheet, with strong Kingpin bolted and
locked – adjustable, thermoplastic dust protection ring and seal,
wheel axle bolted, adjustable total lock – leading or trailing
available

Advantages

- ✓ electrically conductive
- ✓ excellent running performance
- ✓ low rolling resistance
- ✓ good abrasion resistance
- ✓ korrosionsbeständig
- ✓ non-marking

Applications

- Trash container trucks
- Dollies



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
KD 125 ELPGB	Swivel castor	125x40	225	163	135x110	105x80	10,5	106		92,64
KDT 125 ELPGB	Swivel castor with total lock	125x40	225	163	135x110	105x80	10,5	140		117,12
KDF 125 ELPGB	Fixed castor	125x40	225	163	135x110	105x80	10,5			73,08
KD 160 ELPGK	Swivel castor	160x45	300	199	135x110	105x80	10,5	130		128,04
KDT 160 ELPGK	Swivel castor with total lock	160x45	300	199	135x110	105x80	10,5	140		149,64
KDF 160 ELPGK	Fixed castor	160x45	300	199	135x110	105x80	10,5			106,68
KD 200 ELPGK	Swivel castor	200x50	450	249	135x110	105x80	12,5	167		168,84
KDT 200 ELPGK	Swivel castor with total lock	200x50	450	249	135x110	105x80	12,5	170		208,92
KDF 200 ELPGK	Fixed castor	200x50	450	249	135x110	105x80	12,5			137,88