

Wheels Series CG



max 280 kg -20 °C - +60 °C 80-200 mm

++

swivels easily

++

wear resistant

++

shock proof

+++

floor protective

++

weather proof



Material

Elastic solid rubber tyre, grey, 75±5 Shore A
Revited steel rim, zinc-plated

Advantages

- ✓ non-marking – floor protective
- ✓ excellent running performance
- ✓ very silent in motion
- ✓ low rolling resistance
- ✓ good abrasion resistance

Applications

- Bins
- Refuse bins
- Trash containers
- Refuse containers

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	HUB WIDTH MM	FIXING LENGTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
80 CGB 12	Wheel	80x25	60	40	40		12	12,36
100 CGK 8	Wheel	100x30	90	41	41		8	21,96
100 CGB 12	Wheel	100x30	90	40	40		12	14,16
125 CGK 8	Wheel	125x38	145	41	41		8	27,00
125 CGB 12	Wheel	125x38	145	40	40		12	18,60
150 CGK 10	Wheel	150x40	200	51	51		10	35,40
150 CGB 15	Wheel	150x40	200	50	50		15	27,00
160 CGK 10	Wheel	160x40	210	51	51		10	37,80
160 CGB 15	Wheel	160x40	210	50	50		15	28,08
200 CGK 12	Wheel	200x50	280	61	61		12	58,92
200 CGB 20	Wheel	200x50	280	60	60		20	44,28