

Wheels Series VKRK



max 210 kg -40 °C - +85 °C 40-100 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof



Material

Vulkollan® 92° Shore, vulcanised on core
steel core, precision ball bearing

Advantages

- ✓ maximum service life
- ✓ no deformation during dynamic loads
- ✓ minimum rolling resistance
- ✓ outstanding resistance against oils, petrol, benzene and the majority of acids
- ✓ with Stabaxol high hydrolysis reliability
- ✓ high groove resistance
- ✓ no deformation during stationary loads
- ✓ excellent temperature stability

Applications

- Haulage way
- Assembly lines
- Mechatronik

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	HUB WIDTH MM	FIXING LENGTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
40X25 VKRK 10	Guide Roller	40x25	60		8		10	45,00
50X15 VKRK 10	Guide Roller	50x15	85		9		10	45,12
50X18 VKRK 17	Guide Roller	50x18	95		10		17	45,48
50X20 VKRK 12	Guide Roller	50x20	100		10		12	47,64
60X20 VKRK 17	Guide Roller	60x20	120		12		17	51,24
60X20 VKRK 20	Guide Roller	60x20	120		12		20	48,96
70X20 VKRK 20	Guide Roller	70x20	130		12		20	53,76
70X25 VKRK 20	Guide Roller	70x25	150		14		20	51,72
70X25 VKRK 25	Guide Roller	70x25	150		15		25	54,96
80X20 VKRK 25	Guide Roller	80x20	150		15		25	57,24
80X25 VKRK 25	Guide Roller	80x25	170		15		25	110,28
100X25 VKRK 25	Guide Roller	100x25	210		15		25	86,52