


# Swivel castor 320 PT 50 TPK

Institutional Series 320P - Wheel TP

 -20 °C - +60 °C

 **swivels easily**

 **wear resistant**

 **shock proof**

 **floor protective**

 **weather proof**

## Wheel



Tread: Thermoplastic elastomer coating 95±3 Shore A\*\*

High quality nylon wheel centre

## Fork



Finish: zinc plated and chromate coated, large double ball bearing, revited, wheel axle bolted and locked, wheel-/total lock – spring stainless steel

Swivel castor	Wheel-Ø A x width B mm: 50x18+18
---------------	----------------------------------

Load Capacity kg:	60
-------------------	----

Load capacity tested according to EN 12530 and EN 12527	
---	--

Overall height H mm:	70
----------------------	----

Dimension of top plate TP mm:	58x58
-------------------------------	-------

Hole spacing HS mm:	40x40/42x42
---------------------	-------------

Hole-Ø HD mm:	6,2
---------------	-----

Swivel radius SR mm:	53
----------------------	----

Wheel bearing:	Ball bearing
----------------	--------------

## Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high resistance to shocks
- ✓ non-marking
- ✓ easy to clean
- ✓ good chemical resistance

## Applications

- Portable bar units
- Metal-Technology
- Kitchen equipment
- Workshops
- Book carts
- Laboratory equipment
- Room service carts
- Instrument stands
- Diagnostic equipment
- School furniture
- Automobile test equipment
- Carpentry

 **ROLLENBAU**

