


Fixed castor CDF 80 CGB

Transport Series CD - Wheel CG

 -20 °C - +60 °C


 swivels easily


 wear resistant


 shock proof


 floor protective


 weather proof

Wheel



Elastic solid rubber tyre, grey, 75±5 Shore A

Revised steel rim, zinc-plated

Fork


 Finish: electro-zinc plated, double ball bearing – revised,
 hardened steel balls thermoplastic dust protection ring, wheel
 axle bolted, total lock

| | |
|---|-------------------------------|
| Fixed castor | Wheel-Ø A x width B mm: 80x30 |
| Load Capacity kg: | 70 |
| Load capacity tested according to EN 12530 and EN 12527 | |
| Overall height H mm: | 106 |
| Dimension of top plate TP mm: | 102x83 |
| Hole spacing HS mm: | 80x60 |
| Hole-Ø HD mm: | 9 |
| Wheel bearing: | Roller bearing |

Advantages

- ✓ non-marking – floor protective
- ✓ excellent running performance
- ✓ very silent in motion
- ✓ low rolling resistance
- ✓ good abrasion resistance

Applications

- Caddies
- Platform trucks
- Mobile tool racks
- Flight cases
- Bins
- Tow line trucks
- Tow-line trucks
- Chair dollies
- Table dollies
- Furniture dollies
- Refuse bins
- Delivery containers
- Diagnostic equipment
- Dollies
- Automobile test equipment
- Trash containers
- Refuse containers

