Product data sheet Fixed castor EDDF 180 EEK

Extra Heavy Duty Series EDD - Wheel E

-30 °C - +80 °C



Wheel



Tread: Elastic solid rubber tyre, black, 73 ± 5 Shore A, vulcanised on wheel centre



Wheel centre: Die-cast aluminium alloy

Fork



For applications where a super strong and durable caster is required, one tapered roller and one axial ball bearing, dust protection ring, very strong integrated Kingpin, locked nut, grease nipple, wheel axle bolted, finish – painted

Fixed castor	Wheel- \varnothing A x width B mm: 180x50+50
Load Capacity kg:	700
Load capacity tested according to EN 12530 and EN 12527	
Overall height H mm:	260
Dimension of top plate TP	255x205
mm:	
Hole spacing HS mm:	210x160
Hole-Ø HD mm:	17
Wheel bearing:	Ball bearing


Advantages

- excellent running performance
- very silent in motion
- Iow rolling resistance
- good abrasion resistance
- corrosion resistant
- 🔽 non-marking in grey

©Copyright 2024 Rollenbau GmbH, www.rollenbau.at 20.05.2024

⊙ ROLLENBAU





Applications

- Metal-Technology
- Heavy duty dollies
- Trash container trucks
- Machinery moving dollies
- Workshops
- Racks
- Building-Industry