


# Levelling Castor HRL M10 40 P

Levelling Castor Series HRL - Wheel P

 -30 °C - +80 °C

+++  
swivels easily

+++  
wear resistant

+++  
shock proof

++  
floor protective

++  
weather proof

## Wheel



Casted high quality nylon wheel  
Steel housing - zinc plated  
double ball race,  
levelling foot reinforced nylon with  
NBR rubber pad, Ø 40 mm  
axle length: 100 mm

- low overall height
- very good manoeuvrability


Levelling Castor	Wheel-Ø A x width B mm: 40x15+15
Load Capacity kg:	100
Load capacity tested according to EN 12530 and EN 12527	
Overall height H mm:	65-69
Threat mm:	M10x20
Swivel radius SR mm:	60
Wheel bearing:	Plain bearing

## Advantages

THE LEVELLING CASTOR WITH INTEGRATED, ADJUSTABLE MOUNT PROVIDES PERFECT STABILITY. The change from "ROLLING" to "LEVELLING" can take place to a large extent manually. For the last turn a spanner will be required. In the position "levelling", the housing is free of load and can be turned.

- ✓ easy running on smooth floors
- ✓ impact proof
- ✓ high abrasion resistance
- ✓ easy to clean
- ✓ high chemical resistance

©Copyright 2024 Rollenbau GmbH, [www.rollenbau.at](http://www.rollenbau.at) 03.06.2024



## Applications

- Decoration carts
- Stage equipment