

# Fixed castor EDF 200 TLK

Extra Heavy Duty Series ED - Wheel TL



-30 °C - +80 °C

  
swivels easily


  
wear resistant


  
shock proof


  
floor protective


  
weather proof

## Wheel



Tread: cast polyurethane, 95±3 Shore A

Core: De-cast aluminium alloy

## Fork



For applications where a super strong and durable caster is required,  
one tapered roller and one axial ball bearing,  
dust protection ring,  
very strong integrated Kingpin,  
locked nut, grease nipple, wheel axle bolted,  
finish – painted

Fixed castor	Wheel-Ø A x width B mm: 200x50
Load Capacity kg:	800
Load capacity tested according to EN 12530 and EN 12527	
Overall height H mm:	251
Dimension of top plate TP mm:	135x110
Hole spacing HS mm:	105x80
Hole-Ø HD mm:	13
Wheel bearing:	Ball bearing

## Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ good chemical resistance

## Applications

- Metal-Technology
- Heavy duty dollies
- Trash container trucks
- Machinery moving dollies
- Workshops
- Racks
- Building-Industry
- Carpentry

