

# Swivel castor with total lock CST 125 EK

Transport Series CD - Wheel E

 -20 °C - +70 °C

|   |   |  |
|---|---|--|
| <br>swivels easily   | <br>wear resistant | <br>shock proof |
| <br>floor protective | <br>weather proof  |  |

## Wheel



Tread: Elastic solid rubber tyre, black, 73±5 Shore A, vulcanised on wheel centre

Wheel centre: Die-cast aluminium alloy

## Fork



Finish: electro-zinc plated, double ball bearing – revited, hardened steel balls thermoplastic dust protection ring, wheel axle bolted, total lock

|  |              |
|--|--------------|
| Swivel castor with total lock Wheel-Ø A x width B mm: 125x50 |              |
| Load Capacity kg:  | 170          |
| Load capacity tested according to EN 12530 and EN 12527      |              |
| Overall height H mm:   | 160          |
| Dimension of top plate TP mm:                                | 102x83       |
| Hole spacing HS mm:  | 80x60        |
| Hole-Ø HD mm:  | 9            |
| Swivel radius SR mm:   | 140          |
| Wheel bearing:   | Ball bearing |

## Advantages

-  excellent running performance
-  very silent in motion
-  low rolling resistance
-  good abrasion resistance
-  corrosion resistant
-  non-marking in grey



## Applications

- Bins
- Refuse bins
- Dollies
- Trash containers
- Refuse containers