


Press-on-Tyres VK200/75/100

additional articles Series VK - Wheel BANDAGEN

 -40 °C - +85 °C

+

+

swivels easily

+

+

wear resistant

+

+

shock proof

+

+

floor protective

+

+

weather proof

Wheel

VULKOLLAN® 93± 3 Shore A, cylindrical with steel band*Also available: • press-on tyres without steel band • conical tyres • polyurethane tyres 95±3 Shore ATread L = smooth P = profileinner Tolerances according to DIN ISO 286OTHER DIMENSIONS AVAILABLE ON REQUESTPolyurethane rods and tubesØ 16mm - Ø125 mm



Press-on-Tyres	Wheel-Ø A x width B mm: 200
Inner-Ø mm:	100
Load Capacity kg:	1000
Load capacity tested according to EN 12530 and EN 12527	
Tread:	L
Fork Lift:	Lansing - Mic

Advantages

- ✓ high load capacity
- ✓ long service life
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ excellent temperature stability
- ✓ no deformation during longperiod stationary loads
- ✓ outstanding resistance against UV-radiation, oils, greases, petrol and the majority of acids

Tread L = smooth P = profile

©Copyright 2024 Rollenbau GmbH, www.rollenbau.at 02.05.2024

Applications

- Fork-lifts