
Product data sheet

Press-on-Tyres VK250/50/190 additional articles Series VK - Wheel BANDAGEN

-40 °C - +85 °C



Wheel

VULKOLLAN® 93± 3 Shore A, cylindrical with steel band*Also available: • press-on tyres without steel band • conical tyres • polyurethane tyres 95±3 Shore ATread L = smooth P = profileinner Tolerances according to DIN ISO 2860THER DIMENSIONS AVAILABLE ON REQUESTPolyurethane rods ans tubesØ 16mm - Ø125 mm

<mark>⊙ | ROLLENBAU</mark>



Press-on-Tyres	Wheel- \emptyset A x width B mm: 250
Inner-Ø mm:	190
Load Capacity kg:	900
Load capacity tested according to EN 12530 and EN 12527	
Tread:	L
Fork Lift:	Datsun

Advantages

- high load capacity
- Iong service life
- Iow rolling resistance
- high abrasion and tear resistance
- high resistance to shocks
- excellent temperature stability
- no deformation during longperiod stationary loads
- outstanding resistance against UV-radiation, oils, greases, petrol and the majority of acids

Tread L = smooth P = profile

©Copyright 2024 Rollenbau GmbH, www.rollenbau.at 05.05.2024

Applications

- Fork-lifts