


Press-on-Tyres VK254/76/203P

additional articles Series VK - Wheel BANDAGEN

 -40 °C - +85 °C

++

swivels easily

++

wear resistant

++

shock proof

++

floor protective

++

weather proof



Wheel

VULKOLLAN® 93± 3 Shore A, cylindrical with steel band*Also available: • press-on tyres without steel band • conical tyres • polyurethane tyres 95±3 Shore ATread L = smooth P = profileinner Tolerances according to DIN ISO 286OTHER DIMENSIONS AVAILABLE ON REQUESTPolyurethane rods and tubesØ 16mm - Ø125 mm

Press-on-Tyres	Wheel-Ø A x width B mm: 254
Inner-Ø mm:	203,2
Load Capacity kg:	1600
Load capacity tested according to EN 12530 and EN 12527	
Tread:	P
Fork Lift:	Lansing

Advantages

- ✓ high load capacity
- ✓ long service life
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ excellent temperature stability
- ✓ no deformation during longperiod stationary loads
- ✓ outstanding resistance against UV-radiation, oils, greases, petrol and the majority of acids

Applications

- Fork-lifts

Tread L = smooth P = profile